

FirePro Systems Limited

6 Koumandarias & Spyrou Araouzou Street
 Tonia Court No.2, 6th Floor, CY-3036 Limassol
 P. O. Box 54080, CY-3720 Limassol, CYPRUS
 Tel: +357 25 379 999, Fax: +357 25 354 432

Web: www.firepro.info, email: mail@firepro.info

An ISO 9001:2008 & 14001:2004 registered company

FirePro®

Manufacturer &
 Worldwide Supplier of
 Fire Extinguishing
 Aerosol Systems

Technical Data Sheet

<p style="text-align: center;">FP-200S</p> 	TECHNICAL INFORMATION	
	Model	FP-200S
	Type	Cold
	Activation mechanism	thermal activation by thermocord at 172 °C electrical (6 - 36 V D/C 0.8 A in 3 - 4 sec)
	Activator type	heating element with 2.3 ohm resistance
	Current intensity to be tested	maximum 5 mA
	Weight gross	1630 g
	Weight net extinguishing agent	200 g
	Operational discharge time	5 - 10 seconds
	Nozzle	Optional
	Discharge outlet	1
	Discharge length	2 m
	Size	150 mm x 84 mm (incl. connector housing)
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
	Rooms Transport Storage Large switch rooms Cabinets Transformers (large)	server rooms, ceilings, floors car, lorry, bus, train, metro, tram cupboards, safes meter cupboards, control units electrical cabinets industry



FirePro Systems Limited, www.firepro.info, mail@firepro.info

