

FirePro Systems Limited

6 Koumandarias & Spyrou Araouzou Street
 Tonia Court No.2, 6th Floor, CY-3036 Limassol
 P. O. Box 54080, CY-3720 Limassol, CYPRUS
 Tel: +357 25 379 999, Fax: +357 25 354 432

Web: www.firepro.info, email: mail@firepro.info

An ISO 9001:2008 & 14001:2004 registered company

FirePro®

Manufacturer &
 Worldwide Supplier of
 Fire Extinguishing
 Aerosol Systems

Technical Data Sheet

<p style="text-align: center;">FP-80S</p> 	TECHNICAL INFORMATION	
	Model	FP-80S
	Type	Cold
	Activation mechanism	thermal activation by thermocord at 172 °C electrical (6 - 36 V D/C 0.8 A in 3 - 4 sec)
	Activator type	heating element with 2.3 ohm resistance
	Current intensity to be tested	maximum 5 mA
	Weight gross	820 g
	Weight net extinguishing agent	80 g
	Operational discharge time	5 - 10 seconds
	Discharge outlets	2
	Discharge length	2 m
	Size	185 mm x 51 mm (incl. connector housing)
	Self activation temperature	300 °C
	Fire class	A, B, C, F
	APPLICATIONS	
	Hardware Cabinets Sound installations Instrumentation Switch boxes (medium) Transformers (medium)	computers, teleph. exchanges electrical cabinets amplifiers, mixing desks, speakers mechanical machines relay boxes, meter cupboards (small) portable welders

