



- **1/3" SONY Super HAD II CCD**
- **Resolution: 580TVL**
- **Built-in OSD menu**
- **DNR, SBLC, Mirror function and Sens-up function**
- **Privacy Zone, Motion Detection**
- **Digital Wide Dynamic Range Expansion**
- **IR leds: 18x05, IR distance: 15~20m**
- **Vandal-proof, 3-axis bracket adjustable, IP66**
- **DC12V**

FC CE MA RoHS

Spécifications

Pick-up Device	1/3" SONY Super HAD II CCD
Effective Pixels	NTSC:768x494,PAL:752x582
Resolution	580TVL
Scan System	2:1Interlace
Sensor Size	4.9mm*3.7mm
Sync system	Internal
Min.illumination	0lux(IR ON)
S/N Ratio	50dB(AGC OFF)
Electronic Shutter	Anti-flicker/Auto/Manual/Fixed
Lens	2.8~11 auto iris lens
Mirror Function	Mirror/Vertical Mirror/ OFF
Privacy Zone	OFF/ ON (8Zones)
BLC	HSBLC/BLC/OFF
Motion detection	OFF/ ON (4 Zones)
D-WDR	INDOOR/OUTDOOR/OFF
3DNR	OFF/ON
D-Zoom	OFF/ON
Image Freeze	OFF/ON
Gamma	0,45
White Balance	ATW/AWT/AWC-SET/MANUAL/INDOOR/OUTDOOR
AGC	HIGH/MIDDLE/LOW/OFF
Video Output	1.0Vp-p Composite Video Output, 75 Ohm
IR Distance	15~20m
Power Supply	DC12V±10%
Power Consumption(Max)	120mA/260mA(IR on)
Operation temp	-20°C ~ 50°C

Dimensions

