



- **1/3" SONY Super HAD CCD**
- **Resolution: 540TVL**
- **Color: 0.2Lux/F1.2; B/W: 0.02Lux/F1.2**
- **OSD menu, mirror function and anti-flicker**
- **Motion detect, privacy zone,**
- **Electronic shutter adjustable**
- **3-axis bracket adjustable, vandal-proof, IP66, DC12V**

FC CE MA RoHS

Spécifications

Pick-up device	1/3" SONY Super HAD CCD
Effective pixel	NTSC:768*494,PAL:752*582
Resolution	540TVL
Min. illumination	Color: 0.2Lux/F1.2; B/W: 0.02Lux/F1.2
Sensor size	4.9mm*3.7mm
Sync system	Internal
S/N ratio	More than 48dB
Electronic shutter	Anti-flicker/manual/fixed
Lens	2.8~11mm auto iris lens
Anti-flicker mode	On/off
Mirror function	On/off
Privacy zone	On /Off(4 AREA)
BLC	On /Off(64 AREA)
Motion detect	On /Off(64 AREA)
Gamma	Auto/manual
White balance	Auto(ATW/AWB/MANUAI/FIXED)
AGC control	On/off(0-255)
Day&Night	Color/ B/W / Auto
Video output	1.0Vp-p Composite Video Output, 75 Ohm
Power supply	DC12V±10%
Power consumption(Max)	100mA
Operation temp	-20°C ~ 50°C

Dimensions

