



## KB-701S

3D Control Keyboard for PTZ Speed Dome

### Features

- 3 stage joystick control
- Multi-function keyboard
- Support RS485 and RS232 communication
- RJ45 connector and terminal block for RS485
- Set the address range of the dome camera: 0-255
- Speed level adjustable
- Designate part of image swapping function
- Directly control full functions of speed dome camera



3D Joystick Twist to zoom in and out

### Specification

<b>Model No.</b>	KB701S
<b>Camera types</b>	Speed dome (all functions)
<b>On screen display</b>	All functions
<b>Zoom</b>	All lens functions
<b>Video multiplexer</b>	All functions
<b>Baud rates</b>	2400, 4800, 9600 Bps
<b>Signal</b>	RS-485 Multi-port Half Duplex
<b>Power input</b>	DC Jack
<b>RS485 input</b>	Terminal Block / RJ-45Jack
<b>Input voltage</b>	12V DC (-15/+50%)
<b>Power consumption</b>	3 Watts
<b>Approvals</b>	CE and FCC
<b>Dimension</b>	330(W) x 43(H) x 190(D)mm
<b>Weight</b>	1106 g
<b>Operating temperature</b>	0°C to +40°C
<b>Humidity</b>	10%~90% RH
<b>Storage temperature</b>	-10 to +60C
<b>Effective range</b>	1200 meters (max)