

**DDNS The Simplest Network Setting**

## PRO-HRD SERIES



**PRO-HRD04**

**PRO-HRD08**

**PRO-HRD16**

















# 1920 X 1080 HD display DVR

- Support YPbPr or HDMI output, connected with big size HD TV perfectly, resolution is 1920×1080.
- Up to 16 channels D1 Real-time recording and 16 channels playback at the same time.
- Supply BUILT-IN DDNS domain name.
- Support five OS for mobile surveillance.
- Powerful CMS.
- Support 16 users network view simultaneously.
- Support up to eight 2000G HDD.

**OS Linux interface graphique et CMS en Français  
256 caméras simultanément à l'écran**



# 1920 X 1080 HD display DVR

 MOBILE	 CMS
 H.264	 HDMI
 IE	 MOTION
 SCHEDULE	 PRE-RECORD
 AUDIO	 MOUSE
 PTZ	 DVD-RW
 USB	 GUI
 SATA	 VGA

Model Specification	PRO-HRD04	PRO-HRD08	PRO-HRD16
<b>Channel &amp; Compression</b>	4CH H.264	8CH H.264	16CH H.264
Video format	NTSC / PAL		
Video input	BNC × 4 (1.0V p-p/75 Ω)	BNC × 8 (1.0V p-p/75 Ω)	BNC × 16 (1.0V p-p/75 Ω)
Video output	BNC × 1 (1.0V p-p/75 Ω), VGA X 1, HDMI × 1, YPbPr × 1		
Spot output	BNC × 1 (1.0V p-p/75 Ω)		
LOOP output	BNC × 4 (1.0V p-p/75 Ω)	BNC × 8 (1.0V p-p/75 Ω)	BNC × 16 (1.0V p-p/75 Ω)
HDMI output resolution	1920 × 1080i50 / 1920 × 1080i60		
YPbPr output resolution	1920 × 1080i50 / 1920 × 1080i60		
VGA output resolution	1280 × 1024		
Live output mode	All channels are double field.		
D1 record frame rate	100fps(PAL)/120fps(NTSC)	200fps(PAL)/240fps(NTSC)	400fps(PAL)/480fps(NTSC)
CIF record frame rate	Not support		
D1 Playback frame rate	100fps(PAL)/120fps(NTSC)	200fps(PAL)/240fps(NTSC)	400fps(PAL)/480fps(NTSC)
CIF Playback frame rate	Not support		
Network resolution/fps	CIF>10 fps for each channel		
Audio	RCA × 4input, RCA × 1output	RCA × 8input, RCA × 1output	RCA × 16input, RCA × 1output
Alarm input	4 channel	8 channel	16 channel
Alarm output	Relay output, Normal open (NO), Normal close (NC), COM		
Alarm mode	sensor input alarm, disk full alarm, motion detection alarm, video loss alarm		
Record mode	Time/sensor/motion detection		
Network port	100M RJ-45		
USB port	Two USB 2.0host		
Hard disk	SATA port, support eight 2000G SATA hard disk		
DVD-RW	Optional		
PTZ	RS-485		
Remote control/USB mouse	YES		
Power supply	220V/110V		
Power (without hard disk)	<15W	<40W	<50W
Operating temperature	-10°C—+50°C		
Operating Humidity	10%—90%		
Weight	About 8kg with package		
Dimension	435mm(L)X415mm(W)X103mm(H)		

NOTE : PAL D1 resolution, 720\*576, CIF, 352\*288  
NTSC D1 resolution, 720\*480, CIF, 352\*240

BlackBerry.



**SPECIALIZE**  
**CCTV**  
[www.pro-cctv.com](http://www.pro-cctv.com)