

DDNS The Simplest Network Setting

PRO-VR SERIES



PRO-VR04

PRO-VR08

PRO-VR16

1280 X 1024 HD display DVR

- VGA output resolution is 1280×1024.
- Up to 16 channels CIF Real-time recording and 16 channels playback at the same time.
- 4Ch DVR support D1 Real-time recording, 8/16Ch DVR support D1 non-Real-time recording, each channel is 6 frames.
- Supply BUILT-IN DDNS domain name.
- Support five OS for mobile surveillance.
- Powerful CMS.
- Support 16 users network view simultaneously.
- 16 Channels DVR support YPbPr or HDMI output

**OS Linux interface graphique et CMS en Français
256 caméras simultanément à l'écran**



1280 X 1024 HD display DVR



MOBILE



CMS



H.264



MOTION



IE



PRE-RECORD



SCHEDULE



MOUSE



AUDIO



DVD-RW



PTZ



GUI



USB



VGA



SATA

Model Specification	PRO-VR04	PRO-VR08	PRO-VR16
Channel & Compression	4CH H.264	8CH H.264	16CH H.264
Video format	NTSC / PAL		
Video input	BNC × 4 (1.0V p-p/75 Ω)	BNC × 8(1.0V p-p/75 Ω)	BNC × 16 (1.0V p-p/75 Ω)
Video output	VR4-8-16: BNC + VGA		VR16: + BNC SPOT + YPbPr
output resolution	1280 × 1024		1920 × 1080
D1 record frame rate	100fps(PAL)/120fps(NTSC)	50fps(PAL)/60fps(NTSC)	100fps(PAL)/120fps(NTSC)
CIF record frame rate	100fps(PAL)/120fps(NTSC)	200fps(PAL)/240fps(NTSC)	400fps(PAL)/480fps(NTSC)
D1 Playback frame rate	25fps(PAL)/30fps(NTSC)	50fps(PAL)/60fps(NTSC)	100fps(PAL)/120fps(NTSC)
CIF Playback frame rate	100fps(PAL)/120fps(NTSC)	200fps(PAL)/240fps(NTSC)	400fps(PAL)/480fps(NTSC)
Network resolution/fps	CIF >10 fps for each channel		
Audio	RCA × 4input, RCA × 1output		
Alarm mode	sensor input alarm, disk full alarm, motion detection alarm, video loss alarm		
Alarm input	4 input		
Alarm output	Relay output, Normal open (NO), Normal close (NC), COM		
Record mode	Time/sensor/motion detection		
Network port	100M RJ-45		
USB port	Two USB 2.0host		
Hard disk	1 × 2000G		
DVD-RW	USB DVD-RW		
PTZ	RS-485		
Remote control	YES		
USB mouse	YES		
Power supply	12V 3A		
Operating temperature	-10°C—+50°C		
Operating Humidity	10%—90%		
Weight	About 3kg with package		
Dimension	338mm(L)X250mm(W)X65mm(H)		

BlackBerry



NOTE : PAL D1 resolution, 720*576, CIF, 352*288
NTSC D1 resolution, 720*480, CIF, 352*240

SPECIALIZE
CCTV
www.pro-cctv.com